## NSN 5930-01-160-0639

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-160-0639

Thread Class:
2a all threaded stud
Inside Diameter:
0.375 inches all connections
Hazardous Locations/environmental Protection:
Dustproof
Distance Between Mounting Facility Centers:
1.230 inches
Pressure Switch Type:
Gage
Mounting Method:
Threaded stud
Features Provided:
Automatic reset
Contact Action Stimulus:
Increase
Thread Size:
0.375 inches all pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
4.00 actuation point pounds per square inch
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:
Plain, threaded internal all connections
Media For Which Designed:
Liquid
Thread Series Designator:
Unf all threaded stud
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-01-160-0639

Pressure Switch - Page 2 of 2



em			

No

Fiig:

A048b0