## NSN 5930-01-160-0958

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-160-0958

## **Body Style:**

Hole mounted

## Hazardous Locations/environmental Protection:

Submersible

## **Overall Length:**

9.620 inches

## **Overall Height:**

3.190 inches

#### **Overall Width:**

2.280 inches

## Actuator Style:

Round

#### Actuator Height:

0.500 inches

#### **Housing Height:**

#### 2.600 inches

Housing Length:

9.620 inches

## Housing Width:

2.250 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.623 inches

#### Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

#### Inclosure Type:

Hermetically sealed

#### **Mounting Method:**

Unthreaded hole

#### Thready Qty Per Inch (tpi):

20

#### Thread Size:

0.250 inches

#### Nonpile-up Contact Arrangement:

3 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

1.500 amperes resistive dc and 5.000 amperes resistive ac

## **Precious Material And Location:**

Contacts silver

## **Thread Series Designator:**

Unc

#### **Terminal Type And Quantity:**

12 screw

# NSN 5930-01-160-0958

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

