NSN 5930-01-160-4952

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-160-4952

Overall Height:
4.750 inches
Overall Width:
2.625 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Mounting Facility Centers:
5.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+3.00/+50.00 actuation point pounds per square inch and +3.00/+50.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:

Gas or liquid

NSN 5930-01-160-4952

Pressure Switch - Page 2 of 2



Sty	le	De	siq	ına	ato	r:
,	_			,		

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0