

View Online at <https://aerobasegroup.com/nsn/5930-01-160-7019>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

1.250 inches

**Overall Height:**

3.430 inches

**Overall Width:**

0.990 inches

**Body Length:**

0.679 inches

**Body Width:**

0.750 inches

**Case Material:**

Metal

**Actuator Length:**

1.000 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.270 inches

**Actuator Width:**

0.750 inches

**Actuator Color:**

Amber single actuator and green single actuator

**Illuminated Actuator Color:**

Amber single actuator and green single actuator

**Actuator Inscription:**

Start run single actuator

**Actuator Color Sequence:**

Upper half of actuator green lower half of actuator amber

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

1 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0