

View Online at <https://aerobasegroup.com/nsn/5930-01-161-3087>

Overall Length:

2.156 inches

Overall Height:

4.406 inches

Overall Width:

1.812 inches

Mounting Slot Width:

0.142 inches

Capillary Tube Length:

15.0 inches

Bulb Length:

3.500 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

1.562 inches

Longest Vertical Distance Between Mounting Centers:

2.938 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

22.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+240.00 actuation point degrees fahrenheit and +100.00/+240.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point screw with scale and internal deactuation point screw with scale

Contact Stimulus Rating:

180.00 actuation point degrees fahrenheit and 174.00 deactuation point degrees fahrenheit and 6.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0