NSN 5930-01-161-3087

Thermostatic Switch - Page 1 of 2

120.0 ac at sea level single voltage



View Online at https://aerobasegroup.com/nsn/5930-01-161-3087

Overall Length:
2.156 inches
Overall Height:
4.406 inches
Overall Width:
1.812 inches
Mounting Slot Width:
0.142 inches
Capillary Tube Length:
15.0 inches
Bulb Length:
3.500 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
1.562 inches
Longest Vertical Distance Between Mounting Centers:
2.938 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Slot
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
22.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+100.00/+240.00 actuation point degrees fahrenheit and +100.00/+240.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
Internal actuation point screw with scale and internal deactuation point screw with scale
Contact Stimulus Rating:
180.00 actuation point degrees fahrenheit and 174.00 deactuation point degrees fahrenheit and 6.00 differential point degrees fahrenheit
Contact Voltage Rating In Volts:

NSN 5930-01-161-3087 Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0