

View Online at <https://aerobasegroup.com/nsn/5930-01-161-4499>

Body Style:

Bushing mount

Bushing Length:

0.352 inches

Body Length:

0.510 inches

Body Width:

0.465 inches

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.410 inches

Actuator Position-action Relationship:

Center position maintained and left position maintained and right position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.525 inches

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Test Data Document:

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

81349-mil-s-83731/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0