

View Online at <https://aerobasegroup.com/nsn/5930-01-161-4503>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

3.190 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Diameter:

1.000 inches

Bushing Length:

0.470 inches

Body Length:

2.030 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

Test Data Document:

81349-mil-s-5594 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 wire lead

Specification Data:

81349-mil-s-5594/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0