## NSN 5930-01-161-4503

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-161-4503 **Thread Class:** 2a **Body Style: Bushing mount Overall Length:** 3.190 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Body Diameter:** 1.000 inches **Bushing Length:** 0.470 inches **Body Length:** 2.030 inches **Case Material:** Metal **Actuator Style:** Round **Actuator Diameter:** 0.240 inches **Actuator Height:** 0.690 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Holding solenoid

Thready Qty Per Inch (tpi): 32

**Thread Size:** 

0.469 inches

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:** 

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

## NSN 5930-01-161-4503

Toggle Switch - Page 2 of 2



## **Test Data Document:**

81349-mil-s-5594 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

| Thread | oenes | Desiui | IALUI . |
|--------|-------|--------|---------|
|        |       | 9.     |         |

Uns

**Terminal Type And Quantity:** 

3 wire lead

**Specification Data:** 

81349-mil-s-5594/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A053a0