

View Online at <https://aerobasegroup.com/nsn/5930-01-161-5850>

Thread Class:

2b 2nd mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

7.055 inches

Overall Height:

2.820 inches

Overall Width:

2.820 inches

Individual Section Quantity:

11

Longest Horizontal Distance Between Mounting Centers:

2.300 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.300 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing w/panel seal 1st mounting facility

Thready Qty Per Inch (tpi):

24 2nd mounting facility

Thread Size:

0.625 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Criticality Code Justification:

Zzzy

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo3313

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 1st mounting facility

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0