

View Online at <https://aerobasegroup.com/nsn/5930-01-161-8148>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.594 inches

Overall Height:

5.562 inches

Overall Width:

2.594 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

3.625 inches

Bulb Diameter:

0.688 inches

Longest Horizontal Distance Between Mounting Centers:

2.719 inches

Longest Vertical Distance Between Mounting Centers:

2.719 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

190.0 degrees fahrenheit

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load third voltage and 10.0 amperes inductive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+80.00/+145.00 actuation point degrees fahrenheit and +40.00/+137.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw with scale and external deactuation point screw with scale

Contact Voltage Rating In Volts:

600.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0