

View Online at <https://aerobasegroup.com/nsn/5930-01-161-8150>

**Thread Class:**

2a single mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

109.0 millimeters

**Overall Diameter:**

57.7 millimeters

**Nonturn Device Radius:**

16.5 millimeters at 12: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 12: 00 o'clock

**End Application:**

2410-01-126-7902 fixed attenuator

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Features Provided:**

Actuator knob and cam actuated and push to turn

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.625 inches single mounting facility

**Contact Voltage Rating In Volts:**

24.0 dc at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Cam Actuated Switch Contact Arrangement:**

1 pole, double throw, one position momentary single switch single section rear

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

100.0 amperes resistive load dc at sea level

**Style Designator:**

Snap or line

**Thread Series Designator:**

Un single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0