

View Online at <https://aerobasegroup.com/nsn/5930-01-161-8150>

Thread Class:

2a single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

109.0 millimeters

Overall Diameter:

57.7 millimeters

Nonturn Device Radius:

16.5 millimeters at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 12: 00 o'clock

End Application:

2410-01-126-7902 fixed attenuator

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Actuator knob and cam actuated and push to turn

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.625 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary single switch single section rear

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

100.0 amperes resistive load dc at sea level

Style Designator:

Snap or line

Thread Series Designator:

Un single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0