

View Online at <https://aerobasegroup.com/nsn/5930-01-161-9511>

**Body Style:**

Bushing mounted

**Overall Length:**

2.540 inches

**Body Diameter:**

0.469 inches

**Bushing Length:**

Between 0.830 inches and 0.890 inches

**Body Length:**

1.100 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

Between 0.510 inches and 0.540 inches

**Actuator Roller Diameter:**

Between 0.391 inches and 0.421 inches

**Actuator Roller Width:**

Between 0.058 inches and 0.064 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

27.2 ounces

**Actuator Movement:**

Between 0.010 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes inductive dc and 2.000 amperes lamp dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0