

View Online at <https://aerobasegroup.com/nsn/5930-01-161-9511>

Body Style:

Bushing mounted

Overall Length:

2.540 inches

Body Diameter:

0.469 inches

Bushing Length:

Between 0.830 inches and 0.890 inches

Body Length:

1.100 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 0.510 inches and 0.540 inches

Actuator Roller Diameter:

Between 0.391 inches and 0.421 inches

Actuator Roller Width:

Between 0.058 inches and 0.064 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

27.2 ounces

Actuator Movement:

Between 0.010 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes inductive dc and 2.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0