

View Online at <https://aerobasegroup.com/nsn/5930-01-162-2951>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Case Material:

Metal

Actuator Length:

3.750 inches

Actuator Style:

Roller arm

Actuator Height:

3.480 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

1.160 inches

Housing Height:

1.780 inches

Housing Length:

2.840 inches

Housing Width:

1.650 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.340 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.160 inches

Maximum Voltage Rating In Volts:

440.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

50.0 pretravel degrees and 15.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

4.500 amperes inductive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0