NSN 5930-01-162-2951

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-162-2951

Padu Chida
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof Coop Materials
Case Material:
Metal
Actuator Length: 3.750 inches
Actuator Style:
Roller arm
Actuator Height:
3.480 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
1.160 inches
Housing Height:
1.780 inches
Housing Length:
2.840 inches
Housing Width:
1.650 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.160 inches
Maximum Voltage Rating In Volts:
440.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
16.0 ounces
Switch Actuating Force:
32.0 ounces
Actuator Movement:
50.0 pretravel degrees and 15.0 overtravel degrees and 4.0 differential degrees

4.500 amperes inductive ac

Contact Load Current Rating At Maximum Rated Voltage:

NSN 5930-01-162-2951

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0