

View Online at <https://aerobasegroup.com/nsn/5930-01-162-3677>

**Hazardous Locations/environmental Protection:**

Humidity resistant and vibration resistant

**Overall Height:**

1.156 inches

**Mounting Slot Width:**

0.125 inches

**Body Height:**

0.677 inches

**Overall Diameter:**

1.061 inches

**Distance Between Mounting Facility Centers:**

1.375 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -10.0 degrees fahrenheit and 220.0 degrees fahrenheit

**Mounting Method:**

Bracket and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 2.9 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

62.00 actuation point degrees fahrenheit and 22.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

240.0 ac at sea level second voltage

**Special Features:**

Wire lead terminals 8.000 in. Lg

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0