

View Online at <https://aerobasegroup.com/nsn/5930-01-162-4065>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

General purpose-nema type 1

Overall Length:

3.188 inches

Overall Height:

4.906 inches

Overall Width:

1.562 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.190 inches

Distance Between Mounting Facility Centers:

2.562 inches

End Application:

Radar and communications signal simulator station an/ssq-74

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

250.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+200.00 actuation point pounds per square inch and +0.00/+200.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Stimulus Rating:

4.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0