

View Online at <https://aerobasegroup.com/nsn/5930-01-162-4070>

**Body Style:**

Bushing mounted

**Bushing Length:**

0.500 inches

**Body Length:**

0.578 inches

**Body Width:**

0.781 inches

**Body Height:**

0.625 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.281 inches

**Actuator Height:**

0.359 inches

**Actuator Free Position Height:**

0.359 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

16.0 ounces

**Actuator Movement:**

Between 0.025 pretravel inches and 0.250 overtravel inches and 0.003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0