

View Online at <https://aerobasegroup.com/nsn/5930-01-162-4070>

Body Style:

Bushing mounted

Bushing Length:

0.500 inches

Body Length:

0.578 inches

Body Width:

0.781 inches

Body Height:

0.625 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.281 inches

Actuator Height:

0.359 inches

Actuator Free Position Height:

0.359 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

Between 0.025 pretravel inches and 0.250 overtravel inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0