## NSN 5930-01-163-3197

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-163-3197

| Overall Length:   |
|---|
| 3.750 inches  |
| Body Length:  |
| 0.900 inches  |
| End Application:  |
| 2350-00-808-7100 tractor, full track  |
| Pressure Switch Type:   |
| Gage  |
| Width Across Flats:   |
| 0.750 inches  |
| Operating Tempurature Rating:   |
| Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit   |
| Mounting Method:  |
| Clamp   |
| Thready Qty Per Inch (tpi):   |
| 18 single pressure connection   |
| Contact Action Stimulus:  |
| Increase  |
| Thread Size:  |
| 0.250 inches single pressure connection   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, normally closed, momentary action   |
| Terminal Type:  |
| Connector, plug   |
| Contact Load Current Rating:  |
| 7.0 amperes resistive load second voltage and 4.0 amperes inductive load second voltage   |
| Contact Adjustability:  |
| Deactuation point not adjustable and actuation point not adjustable   |
| Contact Stimulus Rating:  |
| 82.00 actuation point pounds per square inch gage and 77.00 deactuation point pounds per square inch gage and 5.00 differential point |
| pounds per square inch gage   |
| Contact Voltage Rating In Volts:  |
| 28.0 dc at sea level second voltage   |
| Pressure Connector Type:  |
| Inverted flare, threaded external single connection   |
| Media For Which Designed:   |
| Gas or liquid   |
| Thread Series Designator:   |
| Npt single pressure connection  |
| Shelf Life:   |
| N/a   |

--

**Unit Of Measure:** 

## NSN 5930-01-163-3197

Pressure Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0