

View Online at <https://aerobasegroup.com/nsn/5930-01-163-3722>

**Overall Length:**

1.880 inches

**Outside Diameter:**

0.200 inches all connections

**Overall Height:**

0.491 inches

**Overall Width:**

1.000 inches

**Body Length:**

1.000 inches

**Unthreaded Mounting Hole Diameter:**

0.086 inches

**Longest Horizontal Distance Between Mounting Centers:**

0.781 inches

**Longest Vertical Distance Between Mounting Centers:**

0.781 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -25.0 degrees fahrenheit and 125.0 degrees fahrenheit

**Mounting Method:**

Base and unthreaded hole

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

25.00 pounds per square inch

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

20.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

+0.05/+300.00 actuation point inches of water and +0.05/+300.00 deactuation point inches of water

**Contact Adjustment Type:**

External actuation point screw and external deactuation point screw

**Contact Stimulus Rating:**

0.50 actuation point inches of water and 1.10 actuation point inches of water and 1.20 deactuation point inches of water

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Pressure Connector Type:**

Barbed, unthreaded external all connections

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0