NSN 5930-01-163-4939

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-163-4939

| Thread Class |
|--|
| Thread Class: |
| 2a |
| Overall Length: |
| 1.395 inches |
| Overall Height: |
| 1.015 inches |
| Overall Width: |
| 1.610 inches |
| Bushing Length: |
| 1.000 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.250 inches |
| Actuator Height: |
| 0.380 inches |
| Actuator Free Position Height: |
| 1.380 inches |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Method: |
| Threaded bushing |
| Thread Size: |
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Switch Release Force: |
| 64.0 ounces |
| Switch Actuating Force: |
| Between 96.0 ounces and 144.0 ounces |
| Actuator Movement: |
| Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 500.0 milliamperes resistive dc |
| Thread Series Designator: |
| Unef |
| Terminal Type And Quantity: |
| 1 connector, receptacle |

NSN 5930-01-163-4939

Sensitive Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0