

View Online at <https://aerobasegroup.com/nsn/5930-01-163-6251>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

4.750 inches

**Overall Height:**

2.250 inches

**Overall Width:**

4.120 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.500 inches

**Longest Vertical Distance Between Mounting Centers:**

2.562 inches

**End Application:**

2350-01-110-4660 carrier, cargo

**Pressure Switch Type:**

Gage

**Mounting Method:**

Base and threaded hole

**Features Provided:**

Automatic reset

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Eight position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

+1000.00/+1100.00 actuation point pounds per square inch and +945.00/+1045.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw and external deactuation point screw

**Contact Stimulus Rating:**

1050.00 actuation point pounds per square inch and 995.00 deactuation point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0