NSN 5930-01-163-6251

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-163-6251

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.750 inches

Overall Height:

2.250 inches

Overall Width:

4.120 inches

Longest Horizontal Distance Between Mounting Centers:

3.500 inches

Longest Vertical Distance Between Mounting Centers:

2.562 inches

End Application:

2350-01-110-4660 carrier, cargo

Pressure Switch Type:

Gage

Mounting Method:

Base and threaded hole

Features Provided:

Automatic reset

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Eight position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+1000.00/+1100.00 actuation point pounds per square inch and +945.00/+1045.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Stimulus Rating:

1050.00 actuation point pounds per square inch and 995.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

NSN 5930-01-163-6251

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0