

View Online at <https://aerobasegroup.com/nsn/5930-01-164-2481>

Thread Class:

2a all threaded stud

Thread Length:

0.500 inches all threaded stud

Overall Length:

2.750 inches

Overall Height:

7.406 inches

Overall Width:

2.875 inches

Body Height:

4.531 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

4.468 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

1.906 inches

Longest Vertical Distance Between Mounting Centers:

2.438 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Threaded stud

Features Provided:

Electrical access port and tamper proof cap

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded stud

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+150.00/+350.00 actuation point degrees fahrenheit and +150.00/+350.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob and external actuation point knob

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0