# NSN 5930-01-164-2484

Toggle Switch - Page 1 of 2

Unthreaded hole



View Online at https://aerobasegroup.com/nsn/5930-01-164-2484

| Body Style:   |
|---|
| Hole mount  |
| Overall Length:   |
| 1.156 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.937 inches  |
| Overall Height:   |
| 1.037 inches  |
| Overall Width:  |
| 0.365 inches  |
| Body Length:  |
| 0.500 inches  |
| Body Width:   |
| 0.365 inches  |
| Body Height:  |
| 0.395 inches  |
| Case Material:  |
| Plastic   |
| Unthreaded Mounting Hole Diameter:  |
| 0.094 inches  |
| Actuator Length:  |
| 0.531 inches  |
| Actuator Style:   |
| Pivoted   |
| Actuator Height:  |
| 0.487 inches  |
| Actuator Width:   |
| 0.365 inches  |
| Actuator Position-action Relationship:                                    |
| Up position maintained and down position maintained                       |
| Actuator Color:   |
| White single actuator   |
| Maximum Voltage Rating In Volts:  |
| 250.0 ac and 28.0 dc  |
| End Application:  |
| 5815-01-058-0546 teletypewriter   |
| Mounting Surface To Terminal End Distance:                                |
| 0.550 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |

# NSN 5930-01-164-2484

Toggle Switch - Page 2 of 2



## **Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

#### **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

#### **Precious Material And Location:**

Contacts and terminal surfaces silver

## **Terminal Type And Quantity:**

3 tab, solder lug

o tab, colaci la

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0