NSN 5930-01-164-2488

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-164-2488

·
Body Style:
Panel mounted
Overall Length:
1.875 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Length:
1.785 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Natural single actuator
Actuator Inscription:
Prmtr meas single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Countermeasures set an/slq-34
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Lamp holder and full display lens
Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

NSN 5930-01-164-2488

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Emi shielding

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0