NSN 5930-01-164-5209

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-164-5209

Body Style:				
Panel mount				
Hazardous Locations/environmental Protection:				
Explosion proof				
Overall Length:				
0.750 inches				
Overall Height:				
2.876 inches				
Overall Width:				
0.750 inches				
Body Length:				
0.688 inches				
Body Width:				
0.750 inches				
Case Material:				
Metal				
Actuator Length:				
0.620 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.430 inches				
Actuator Width:				
0.620 inches				
Actuator Color:				
White single actuator				
Illuminated Actuator Color:				
Natural single actuator				
Actuator Inscription:				
On single actuator				
Maximum Voltage Rating In Volts:				
115.0 ac and 28.0 dc				
End Application:				
Countermeasure set an/slq-34				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				
Features Provided:				
Actuator seal				
Nonpile-up Contact Arrangement:				
2 pole, double throw, both positions maintained single switch unit				

NSN 5930-01-164-5209

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious	Material	And	Location:
----------	----------	-----	-----------

Contacts silver

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0