## NSN 5930-01-164-5458

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-164-5458

Overall Length:
3.500 inches
Overall Height:
3.250 inches
Overall Width:
5.250 inches
Body Length:
2.750 inches
Body Width:
5.000 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Mounting Facility Centers:
5.000 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load third voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+10.00/+180.00 actuation point pounds per square inch and +10.00/+180.00 deactuation point pounds per square inch
Contact Adjustment Type:
External actuation point screw and external deactuation point screw

**Contact Voltage Rating In Volts:** 

550.0 dc at sea level fourth voltage

## **NSN 5930-01-164-5458**Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0