NSN 5930-01-164-6870

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-164-6870

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
7.312 inches
Overall Height:
2.500 inches
Overall Width:
2.625 inches
Shaft Length:
2.562 inches single actuator
Unthreaded Mounting Hole Diameter:
0.250 inches single mounting facility
Individual Section Quantity:
3
Longest Horizontal Distance Between Mounting Centers:
0.938 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.688 inches single mounting facility
End Application:
Used onboard 180 ft class coast guard vessels
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section periphery
Throw Quantity:
1 each section front
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and cam actuated
Cubic Measure:
47.985 cubic inches
Contact Voltage Rating In Volts:
600.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Cam Actuated Switch Contact Arrangement:
2 pole, double throw, both positions maintained each switch each section periphery
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator

NSN 5930-01-164-6870

Rotary Switch - Page 2 of 2



Square Shaft Size: 0.250 inches single actuator **Terminal Type:** Screw **Contact Switching Action:** Breaks before makes each section periphery **Switch Actuator Positioning Increment:** 45.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 20.0 amperes resistive load dc at sea level **Special Features:** Name plate inscription "ground light switch" (gls) on-test **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: In-line, cam actuated Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0