NSN 5930-01-164-8261



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-164-8261 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Explosion proof Overall Length: 2.890 inches **Overall Height:** 1.015 inches **Overall Width:** 1.015 inches **Body Diameter:** 1.015 inches **Bushing Length:** 1.000 inches **Body Length:** 1.515 inches **Actuator Style:** Round **Actuator Diameter:** 0.250 inches **Actuator Height:** 0.375 inches **Actuator Free Position Height:** 1.375 inches **Maximum Voltage Rating In Volts:** 28.0 dc **End Application:** F/a-18 Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Release Force:** 64.0 ounces

04.0 0011000

Criticality Code Justification:

Feat

NSN 5930-01-164-8261 Sensitive Switch - Page 2 of 2



Switch Actuating Force:
147.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 0.500 amperes inductive dc
Special Features:
Weapon system essential
Precious Material And Location:
Contacts gold
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A053a0