

View Online at <https://aerobasegroup.com/nsn/5930-01-164-9801>

**Body Style:**

Panel mounted

**Overall Length:**

1.875 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Body Length:**

1.785 inches

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Case Material:**

Metal

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.090 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Natural single actuator

**Actuator Inscription:**

Start test single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Countermeasures set an/slq-34

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Lamp holder and full display lens

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Emi shielding; pb-c sealed with seal kit p/n 50692

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

5 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0