

View Online at <https://aerobasegroup.com/nsn/5930-01-165-1657>

Thread Class:

2a single threaded bushing

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.750 inches

Overall Height:

2.820 inches

Overall Width:

1.280 inches

Body Length:

1.640 inches

Capillary Tube Length:

36.0 inches

End Application:

2310-01-123-2666 truck, ambulance; 2320-01-304-2277 pls (palletized loading system)

Temperature Sensing Element Type:

Capillary tube

Mounting Method:

Threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

6.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+31.00/+43.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point dial

Contact Voltage Rating In Volts:

12.0 dc at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unef single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0