

View Online at <https://aerobasegroup.com/nsn/5930-01-165-2981>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.312 inches 1st mounting facility

Overall Length:

5.262 inches

Overall Height:

2.374 inches

Overall Width:

2.374 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.688 inches single actuator

Nonturn Device Radius:

0.500 inches at 12: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 12: 00 o'clock

Longest Horizontal Distance Between Mounting Centers:

1.375 inches 2nd mounting facility

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded bushing 1st mounting facility

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

212.0 degrees from nonturn device single actuator

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

4.0 amperes resistive load dc at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0