NSN 5930-01-165-5336

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-165-5336

Overall Length: 0.476 inches Overall Height: 0.080 inches Body Diameter: 0.263 inches End Application: 1055-01-092-0596 launcher, rocket Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 300.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Stimulus Rating: 300.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage Frequency In Hertz:
Overall Height: 0.080 inches Body Diameter: 0.263 inches End Application: 1055-01-092-0596 launcher, rocket Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliampers resistive load second voltage Contact Adjustability: Beactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 30.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
0.080 inches Body Diameter: 0.263 inches End Application: 1055-01-092-0959 launcher, rocket Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermelically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 30.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
Body Diameter: 0.263 inches End Application: 1055-01-092-0596 launcher, rocket Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 00.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 30.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
0.263 inches End Application: 1055-01-092-0596 launcher, rocket Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 00.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 30.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
End Application: 1055-01-092-0596 launcher, rocket Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 30.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
1055-01-092-0596 launcher, rocket Tempurature Sensing Element Type: Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Internal sensor Operating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Deprating Tempurature Rating: Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Between 0.0 degrees fahrenheit and 350.0 degrees fahrenheit Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Mounting Method: Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Clamp Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Features Provided: Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Hermetically sealed case Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Increase Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
1 pole, single throw, normally closed, momentary action Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Terminal Type: Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Wire lead Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Contact Load Current Rating: 500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
500.0 milliamperes resistive load second voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Contact Stimulus Rating: 330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
330.00 actuation point degrees fahrenheit and 300.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage
28.0 dc at sea level second voltage
-
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Disc
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-s-24236/13 government specification

N/a

Shelf Life:

NSN 5930-01-165-5336

Thermostatic Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A048b0