

View Online at <https://aerobasegroup.com/nsn/5930-01-165-8755>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and explosion proof

Case Material:

Metal

Actuator Style:

Roller arm

Actuator Height:

1.000 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.320 inches

Housing Height:

2.570 inches

Housing Length:

5.270 inches

Housing Width:

3.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.500 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.360 inches

Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

10.0 pretravel degrees and 40.0 overtravel degrees and 6.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 4.500 amperes resistive ac

Special Features:

Electrical access port

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0