

View Online at <https://aerobasegroup.com/nsn/5930-01-165-8755>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight and explosion proof

**Case Material:**

Metal

**Actuator Style:**

Roller arm

**Actuator Height:**

1.000 inches

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.320 inches

**Housing Height:**

2.570 inches

**Housing Length:**

5.270 inches

**Housing Width:**

3.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

3.500 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

2.360 inches

**Maximum Voltage Rating In Volts:**

440.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

32.0 ounces

**Actuator Movement:**

10.0 pretravel degrees and 40.0 overtravel degrees and 6.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

50.000 milliamperes resistive dc and 4.500 amperes resistive ac

**Special Features:**

Electrical access port

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0