

View Online at <https://aerobasegroup.com/nsn/5930-01-165-9193>

**Thread Length:**

0.312 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

2.600 inches

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Overall Diameter:**

0.750 inches

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

2 each section

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level and 125.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0