NSN 5930-01-166-2913 Rotary Switch - Page 1 of 2



Rolary Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-01-166-2913
Thread Class:
2a single mounting facility
Thread Length:
0.469 inches single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.125 inches
First Flat Length:
0.438 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.625 inches single actuator
Overall Diameter:
2.000 inches
Individual Section Quantity:
6
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
01500-2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
O code costing acco

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

NSN 5930-01-166-2913Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load highest ac voltage rating at sea level
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0