NSN 5930-01-166-2917

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-166-2917
Body Style:
Hole mounted
Overall Length:
2.600 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.990 inches and 1.010 inches
Overall Height:
Between 0.876 inches and 0.886 inches
Overall Width:
Between 0.630 inches and 0.650 inches
Body Length:
1.840 inches
Body Width:
Between 0.630 inches and 0.650 inches
Body Height:
Between 0.630 inches and 0.650 inches
Unthreaded Mounting Hole Diameter:
Between 0.140 inches and 0.150 inches
Actuator Style:
Round
Actuator Diameter:
Between 0.301 inches and 0.311 inches
Actuator Free Position Height:
0.366 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.050 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

NSN 5930-01-166-2917

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0