

View Online at <https://aerobasegroup.com/nsn/5930-01-166-5350>

**Body Style:**

Hole mounted

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

2.200 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.185 inches

**Housing Height:**

1.745 inches

**Housing Length:**

4.444 inches

**Housing Width:**

1.620 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.344 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.156 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 240.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

64.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.190 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 150.000 milliamperes inductive dc and 600.000 milliamperes resistive ac

**Terminal Type And Quantity:**

8 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0