NSN 5930-01-166-5350

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-166-5350 **Body Style:** Hole mounted **Actuator Style:** Roller plunger **Actuator Free Position Height:** 2.200 inches **Actuator Roller Diameter:** 0.500 inches **Actuator Roller Width:** 0.185 inches **Housing Height:** 1.745 inches **Housing Length:** 4.444 inches **Housing Width:** 1.620 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 2.344 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.156 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 240.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 2 two circuit, double break/double make, one position momentary single switch unit **Switch Actuating Force:** 64.0 ounces **Actuator Movement:** Between 0.070 pretravel inches and 0.190 overtravel inches and 0.020 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 400.000 milliamperes resistive dc and 150.000 milliamperes inductive dc and 600.000 milliamperes resistive ac **Terminal Type And Quantity:** 8 screw Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig: A053a0