NSN 5930-01-166-7151

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-166-7151

| Body Style: |
|--|
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Waterproof |
| Overall Length: |
| 2.620 inches |
| Body Diameter: |
| 0.625 inches |
| Overall Diameter: |
| 0.830 inches |
| Actuator Style: |
| Round, flush |
| Actuator Diameter: |
| 0.830 inches |
| Actuator Height: |
| 0.470 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| 3 single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.625 inches |
| Nonpile-up Contact Arrangement: |
| 2 two circuit, double break/double make, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 2.000 amperes inductive dc and 1.500 amperes lamp dc and 3.000 amperes resistive dc and 2.000 amperes inductive ac and 1.500 |
| amperes lamp ac and 3.000 amperes resistive ac |
| Precious Material And Location: |
| Contact and terminal surfaces gold |
| Thread Series Designator: |
| Un |

Terminal Type And Quantity: 6 tab, solder lug

NSN 5930-01-166-7151

Push Switch - Page 2 of 2



| _ | | | - | |
|---|----|-----|---|------|
| C | hΔ | Iŧ. | | ife: |
| • | | | _ | IIC. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0