## NSN 5930-01-167-3413

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-167-3413

**Body Style:** Hole mounted **Overall Length:** 1.488 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.874 inches **Overall Height:** 0.850 inches **Overall Width:** 0.406 inches **Body Length:** 1.094 inches **Body Width:** 0.406 inches **Body Height:** 0.626 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:** 0.122 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.406 inches **Actuator Length:** 0.165 inches **Actuator Style:** Rectangular **Actuator Height:** 0.110 inches **Actuator Width:** 0.110 inches **Actuator Free Position Height:** 0.626 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit

2.0 ounces

**Switch Actuating Force:** 

**Switch Release Force:** 

10.5 ounces

## NSN 5930-01-167-3413

Sensitive Switch - Page 2 of 2



## **Actuator Movement:**

Between 0.063 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

300.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0