

View Online at <https://aerobasegroup.com/nsn/5930-01-167-3414>

Body Style:

Hole mounted

Overall Length:

1.488 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.874 inches

Overall Height:

0.850 inches

Overall Width:

0.406 inches

Body Length:

1.094 inches

Body Width:

0.406 inches

Body Height:

0.626 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.165 inches

Actuator Style:

Rectangular

Actuator Height:

0.110 inches

Actuator Width:

0.110 inches

Actuator Free Position Height:

0.626 inches

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.08 ounces

Switch Actuating Force:

0.54 ounces

Actuator Movement:

Between 0.063 pretravel inches and 0.012 overtravel inches and 0.024 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 100.000 milliamperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0