## NSN 5930-01-167-3414

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-167-3414

Body Style:
Hole mounted
Overall Length:
1.488 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.874 inches
Overall Height:
0.850 inches
Overall Width:
0.406 inches
Body Length:
1.094 inches
Body Width:
0.406 inches
Body Height:
0.626 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.122 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.165 inches
Actuator Style:
Rectangular
Actuator Height:
0.110 inches
Actuator Width:
0.110 inches
Actuator Free Position Height:
0.626 inches
Maximum Voltage Rating In Volts:
125.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit

0.08 ounces

**Switch Release Force:** 

## **NSN 5930-01-167-3414** Sensitive Switch - Page 2 of 2

Fiig: A053a0



Switch Actuating Force:
0.54 ounces
Actuator Movement:
Between 0.063 pretravel inches and 0.012 overtravel inches and 0.024 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
100.000 milliamperes resistive dc and 100.000 milliamperes resistive ac
Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: