

View Online at <https://aerobasegroup.com/nsn/5930-01-167-4189>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

Between 2.220 inches and 2.280 inches

**Overall Height:**

Between 1.775 inches and 1.835 inches

**Overall Width:**

Between 1.120 inches and 1.180 inches

**Unthreaded Mounting Hole Diameter:**

0.090 inches single mounting facility and 0.116 inches single mounting facility

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

2.080 inches single mounting facility and 2.100 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.890 inches single mounting facility and 0.910 inches single mounting facility

**Operating Temperature Range:**

-40.0/+100.0 degrees celsius

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel all actuators

**Features Provided:**

Illuminated

**Contact Voltage Rating In Volts:**

200.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 1st actuator

**Terminal Type:**

Tab, solder lug and wire lead

**Contact Load Current Rating:**

60.0 milliamperes resistive load ac at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 2nd section

**Contact Arrangement Truth Table:**

Bcd with complement, 2 pole - 10 positions each section

**Color:**

White each indicator marking

**Precious Material:**

Gold or rhodium

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0