

View Online at <https://aerobasegroup.com/nsn/5930-01-167-4189>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

Between 2.220 inches and 2.280 inches

Overall Height:

Between 1.775 inches and 1.835 inches

Overall Width:

Between 1.120 inches and 1.180 inches

Unthreaded Mounting Hole Diameter:

0.090 inches single mounting facility and 0.116 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.080 inches single mounting facility and 2.100 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.890 inches single mounting facility and 0.910 inches single mounting facility

Operating Temperature Range:

-40.0/+100.0 degrees celsius

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Features Provided:

Illuminated

Contact Voltage Rating In Volts:

200.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 1st actuator

Terminal Type:

Tab, solder lug and wire lead

Contact Load Current Rating:

60.0 milliamperes resistive load ac at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 2nd section

Contact Arrangement Truth Table:

Bcd with complement, 2 pole - 10 positions each section

Color:

White each indicator marking

Precious Material:

Gold or rhodium

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0